

BACKGROUND OF THE INVENTION

5 The present invention relates to image observation
apparatus for projecting image information directly
onto the retina of an observing eye to permit
observation thereof and an image observation system
using the apparatus, and to image observation apparatus
10 for causing a plurality of parallax images to be
incident on a single eye to permit an observer to
observe a three-dimensional image in a natural state
without causing fatigue of the observer's eye and an
image observation system using the apparatus, which are
5 particularly suitable for three-dimensional display and
three-dimensional observation in a wide angle of view.

The image observation apparatus of the type for directly projecting an image onto the retina has been known heretofore as apparatus for permitting observation of image information based on image display means such as a liquid crystal display panel or the like. For example, the method disclosed in Japanese Patent Publication No. 2679176 permits the observation of image information in similar fashion to the principle of pinhole camera, by illuminating a display element by a point light source and focusing an image

For observation of a stereoscopic image, a pair of image observation devices are provided for the left and right eyes to effect stereoscopic vision by use of binocular parallax. In this construction, focusing conditions of observed images are independent of the accommodation of the eyes. Therefore, this construction can reduce contradiction between convergence and accommodation of the observing eyes in observation of the stereoscopic image by use of only the binocular parallax, so that the observer can observe the stereoscopic image well in the natural state.

The image observation apparatus of the type for directly projecting the image onto the retina is not suitable for observation of image information in a wide angle of view, because the size of an incident beam is fundamentally small at the position of the entrance pupil of the observing eye. This is because, as illustrated in Figs. 38A and 38B, when the eyeball E is rotated around the rotational center C of eyeball so as to gaze at the marginal part of the field, a difference is made in the relation between the rotational center C of eyeball and the position of the pupil P (entrance

Fig. 38A shows a situation in which the eye is
gazing at the center of the field of image information,
wherein display rays 200 travel through the pupil P
without being intercepted by the iris I, to enter the
observing eye E. However, when the eyeball E is
rotated in order to gaze at the marginal part of the
field as illustrated in Fig. 38B, the display rays 200
are intercepted by the iris I to fail to enter the
observing eye E. Symbol L indicates the direction of
the visual axis.

On the other hand, various proposals have been made heretofore on methods of reproducing the

5
10

15

20

25

stereoscopic display with less fatigue of eye is achieved by the "monocular parallax effect" when the conventional stereoscopic display method of presenting parallax images from two view points to the two eyes is extended to a method of presenting parallax images from n view points to n view points and when the distance between two adjacent points of the n view points is set smaller than the observer's pupil.

However, for implementing the stereoscopic display of the "super-multiview regions," it is necessary to present extremely small parallax images to the observer and it thus becomes necessary to handle very huge volumes of image information. In addition, an extremely quick information display means is necessary, because all the parallax images need to be displayed within the permissible time for persistence of vision of the observer's eye.

In Japanese Patent Application No. 2000-28853 filed by Assignee of the present application, we proposed the image observation apparatus capable of implementing the stereoscopic display of "super-multiview regions" without use of very quick image display means and image generating means nor many image display means. This method is characterized in that an exit pupil of a display optical system is optically divided into a plurality of regions, parallax images corresponding to the respective regions are guided to

each observer's eye to cause the parallax images to be incident on the single eye, and image observation devices are provided respectively for the left and right eyes, thereby reducing the number of parallax images to be displayed on each image observation device.

For constructing the image observation apparatus capable of displaying the stereoscopic image in a wide angle of view, it is necessary to set the size of the exit pupil of the display optical system to a large value in order to adapt for movement of the position of the pupil (entrance pupil) with motion of the visual axis for the observer to gaze at the marginal part of the observation field. For example, when the display view angle in the horizontal direction is 2θ as illustrated in Fig. 37, the minimum horizontal width necessary for the exit pupil of the display optical system is given by $2 \times L \times \sin\theta$. Here L indicates the distance between the eyeball rotation center O_1 and the entrance pupil P of the observing eye and is about 10 mm. For example, when $2\theta = 30^\circ$, the horizontal width of the exit pupil is 5.2 mm. When $2\theta = 50^\circ$, the horizontal width is 8.5 mm. In practice, values of about 8 mm and 12 mm are adopted in the cases of $2\theta = 30^\circ$ and $2\theta = 50^\circ$, respectively, including some margins for the above-stated values in consideration of sizes of pupils, deviation upon mounting, and so on.

05030219-042001
100240-6128050

For making a plurality of parallax images incident on a single eye, spacings between centers of the respective regions obtained by dividing the area of the exit pupil into plural regions need to be smaller than
5 the size of the observer's pupil; specifically, about 2 mm, for example, Namely, the size of each region has to be not more than a predetermined size, irrespective of the display view angle.

For the above reasons, many parallax images have
10 to be generated and displayed in order to provide the image observation apparatus permitting the observation of the stereoscopic image in a wide angle of view, and it thus becomes necessary to use very quick image display means and image generating means and many image
15 display means.

Another object of the present invention is thus to provide image observation apparatus being capable of implementing the stereoscopic display of the super-multiview regions in a wide angle of view and thus
20 permitting the observer to observe the stereoscopic image well without fatigue nor dysphoria, and to provide an image observation system using the apparatus.

25 SUMMARY OF THE INVENTION

An image observation apparatus according to an aspect of the present invention is an image observation

100240" 6T22E250

apparatus for observing image information, comprising:

image display means for displaying image
information;

5 a display optical system for projecting the image
information displayed on the image display means, onto
a retina of an observing eye; and

incident beam control means for changing a
position of an incident beam on an entrance pupil of
the observing eye.

10 In a further aspect of the above image observation
apparatus, the position of the incident beam on the
plane of the entrance pupil of the observing eye is
changed by the incident beam control means in
accordance with the image information displayed on the
15 image display means.

In a further aspect of the above image observation
apparatus, the apparatus further comprises pupil
position detecting means for detecting a position of a
pupil of the observer, and the position of the incident
20 beam on the plane of the entrance pupil of the
observing eye is changed by the incident beam control
means, based on information obtained by the pupil
position detecting means.

25 In a further aspect of the above image observation
apparatus, the pupil position detecting means comprises
eyeball illuminating means and light receiving means
for receiving light reflected by the eyeball from

05030219 042001
100240 6120050

illumination light emitted from the eyeball
illuminating means, and the eyeball illumination light
is infrared light.

5 In a further aspect of the above image observation
apparatus, the apparatus comprises illumination means
for illuminating the image display means, an
illumination light source of the illumination means is .
imaged at or near the position of the entrance pupil of
the observing eye by the display optical system, and
10 the position of the incident beam on the plane of the
entrance pupil of the observing eye is changed by
controlling an emission state of the illumination
means.

15 In a further aspect of the above image observation
apparatus, the image display means comprises a
transmission type spatial modulation element.

In a further aspect of the above image observation
apparatus, the image display means comprises a
reflection type spatial modulation element.

20 In a further aspect of the above image observation
apparatus, the illumination means comprises a light-
emitting element array.

In a further aspect of the above image observation
apparatus, the illumination means comprises a surface
25 illuminant and a spatial modulation element.

In a further aspect of the above image observation
apparatus, the illumination means comprises a

042001 6122250

substantially point light source and an optical system having a positive power.

In a further aspect of the above image observation apparatus, the image display means is a self-emission type or light-source-integrated type display element, the image observation apparatus comprises a spatial modulation element for limiting light from the image display means, the spatial modulation element is imaged at or near the position of the entrance pupil of the observing eye by the display optical system, and the position of the incident beam on the plane of the entrance pupil of the observing eye is changed by controlling the spatial modulation element.

In a further aspect of the above image observation apparatus, the spatial modulation element is a transmission type spatial modulation element having a two-dimensional pixel structure.

In a further aspect of the above image observation apparatus, the spatial modulation element is a reflection type spatial modulation element having a two-dimensional pixel structure.

An image observation apparatus according to another aspect of the present invention is an image observation apparatus comprising image display means for displaying a plurality of parallax images, and a display optical system for guiding light from the image display means to an observing eye of an observer, the

09030219"042001
T00240"5T222222

25

to be incident on the single eye of the observer,

wherein a size of the exit pupil of the display optical system is larger than a size of the entrance pupil of the observing eye and a size of a beam from the image display means at the position of the entrance pupil of the observing eye is substantially equal to or smaller than the size of the entrance pupil of the observing eye, and the image observation apparatus comprises control means to change a position of the beam from the image display means at the position of the entrance pupil of the observing eye.

In a further aspect of the above image observation apparatus, the apparatus further comprises pupil position detecting means for detecting the position of the pupil of the observer, and the position of the beam from the image display means at the position of the entrance pupil of the observing eye is changed by the control means, based on information obtained by the pupil position detecting means.

In a further aspect of the above image observation apparatus, the pupil position detecting means comprises eyeball illuminating means and light receiving means for receiving light reflected by the eyeball from illumination light emitted from the eyeball illuminating means, and the eyeball illumination light is infrared light.

In a further aspect of the above image observation

0933219-042001
T000240"6T222260

apparatus, the apparatus comprises illumination means having an illumination light source for illuminating the image display means, the illumination means is located at or near a position optically equivalent to the entrance pupil of the display optical system, the illumination means comprises a plurality of unit light sources, images of the plurality of unit light sources are formed in a plurality of regions in the exit pupil of the display optical system, the exit pupil of the display optical system is spatially divided into a plurality of irradiation regions, and a display image on the image display means is controlled to switch to one corresponding to each irradiation region.

In a further aspect of the above image observation apparatus, the plurality of unit light sources of the illumination light source are comprised of a light-emitting element array.

In a further aspect of the above image observation apparatus, the plurality of unit light sources of the illumination light source are comprised of a surface illuminant and a spatial modulation element.

In a further aspect of the above image observation apparatus, the image display means comprises a plurality of display elements, the image observation apparatus comprises at least one illumination means having an illumination light source for illuminating the plurality of display elements, the illumination

0332219-042004
10040-67225050

light sources are formed in a plurality of regions in the exit pupil of the display optical system, the exit pupil of the display optical system is spatially divided into a plurality of irradiation regions, and parallax images displayed on the plurality of display elements are controlled corresponding to each irradiation region.

15 of regions in the exit pupil of the display optical
system is controlled in time division by controlling in
time division irradiation of beams from a plurality of
unit light sources which an illumination light source
of each illumination means has, and parallax images
20 displayed on the plurality of display elements are
controlled to switch to those corresponding to each
region.

25 illumination light source are comprised of a light-emitting element array.

In a further aspect of the above image observation

In a further aspect of the above image observation

5
10
15
20
25

In a further aspect of the above image observation apparatus, the spatial modulation element is a transmission type spatial modulation element.

In a further aspect of the above image observation apparatus, the spatial modulation element is a reflection type spatial modulation element.

5 In a further aspect of the above image observation apparatus, the display optical system comprises a prism body having a decentered, rotationally asymmetric, reflective surface with optical powers differing depending upon azimuth angles.

10 An image observation system according to one aspect of the present invention is an image observation system comprising a pair of image observation apparatus as set forth, for the left and right eyes of the observer.

15 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an explanatory diagram to illustrate the basic concept of the optical system of image observation apparatus according to an aspect of the present invention;

20 Fig. 2 is an explanatory diagram to illustrate the basic concept of the optical system of image observation apparatus according to the aspect of the present invention;

25 Fig. 3 is an explanatory diagram to illustrate the basic concept of the optical system of image observation apparatus according to the aspect of the present invention;

03838219 042001
T00240 6 T888880

Fig. 5 is an explanatory diagram to illustrate the illumination means in the image observation apparatus of the present invention;

10 Fig. 7 is an explanatory diagram to illustrate the
illumination means in the image observation apparatus
of the present invention;

Figs. 9A, 9B and 9C are explanatory diagrams to illustrate the illumination means in the image observation apparatus of the present invention;

Fig. 11 is a schematic diagram to illustrate the main part of a modification with change in part of Embodiment 1 of the image observation apparatus according to the present invention;

Embodiment 1 of the image observation apparatus
according to the present invention;

Fig. 13 is a schematic diagram to show the main
part of Embodiment 2 of the image observation apparatus
5 according to the present invention;

Fig. 14 is a schematic diagram to illustrate the
main part of a modification with change in part of
Embodiment 2 of the image observation apparatus
according to the present invention;

10 Fig. 15 is a schematic diagram to show the main
part of Embodiment 3 of the image observation apparatus
according to the present invention;

Fig. 16 is a schematic diagram to show the main
part of Embodiment 4 of the image observation apparatus
15 according to the present invention;

Fig. 17 is a schematic diagram to illustrate the
main part of a modification with change in part of
Embodiment 4 of the image observation apparatus
according to the present invention;

20 Fig. 18 is an explanatory diagram to illustrate
the pupil position detecting means of the image
observation apparatus of the present invention;

Figs. 19A and 19B are explanatory diagrams to
illustrate detection of pupil position in the image
25 observation apparatus of the present invention;

Figs. 20A and 20B are explanatory diagrams to
illustrate an input signal into an incident beam

US 3,321,042 A

control circuit in the image observation apparatus of the present invention;

Fig. 21 is an explanatory diagram to illustrate the basic concept of the optical system in the image observation apparatus according to a further aspect of the present invention;

Fig. 22 is an explanatory diagram to illustrate the basic concept of the optical system in the image observation apparatus according to the further aspect of the present invention;

Fig. 23 is an explanatory diagram to illustrate the basic concept of the optical system in the image observation apparatus according to the further aspect of the present invention;

Fig. 24 is an explanatory diagram to illustrate the basic concept of the optical system in the image observation apparatus according to the further aspect of the present invention;

Figs. 25A, 25B and 25C are explanatory diagrams to illustrate the illumination means of the image observation apparatus according to the present invention;

Figs. 26A, 26B and 26C are explanatory diagrams to illustrate the illumination means of the image observation apparatus according to the present invention;

Figs. 27A, 27B and 27C are explanatory diagrams to

03032213 042001
100240 61285850

Fig. 28 is a schematic diagram to show the main part of Embodiment 5 of the image observation apparatus according to the present invention;

Fig. 30 is a schematic diagram to show the main part of Embodiment 6 of the image observation apparatus according to the present invention;

Fig. 32 is a schematic diagram to show the main part of Embodiment 7 of the image observation apparatus according to the present invention;

Fig. 33 is a schematic diagram to show the main part of Embodiment 8 of the image observation apparatus according to the present invention;

Fig. 34 is a schematic diagram to show the main part of Embodiment 9 of the image observation apparatus according to the present invention;

Fig. 35 is a schematic diagram to illustrate the

main part of a modification with change in part of
Embodiment 9 of the image observation apparatus
according to the present invention;

Fig. 36 is an explanatory diagram to illustrate an
5 image observation system of the present invention;

Fig. 37 is an explanatory diagram to illustrate
the relation between the observing eye of the observer
and the range of field; and

Figs. 38A and 38B are explanatory diagrams to show
10 the relation between the observing eye of the observer
and the range of the field.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 to Fig. 3 are explanatory diagrams to
15 illustrate the basic concept of the image observation
apparatus of the present invention.

The image observation apparatus S according to the
present invention is generally provided with an
illumination means 10 having an illumination light
20 source 11, an image display means 20 for displaying
image information 21, a display optical system 30, and
a control means 40.

In Fig. 1, the display optical system 30 forms an
image 11' of the illumination light source 11 at or
25 near the position of the pupil (entrance pupil) P of
the observing eye E. At this time the size of the
illumination light source 11, the position and focal

09333319.042001
T00240"6T28E350

5

15

25

of the image information 21, and the incident beam control circuit 41 controls the illumination means 10 to light up the unit source 11a. The display optical system 30 forms a light source image 11'a on the pupil P of the observing eye E, so that the observer can observe the image 21' formed by the display optical system 30 from the image information 21. When the observer is gazing at the marginal part of the field of the image information 21, as illustrated in Fig. 3, the incident beam control circuit 41 controls the illumination means 10 to light up the unit light source 11b. The display optical system 30 forms a light source image 11'b on the pupil P of the observing eye E, so that the observer can observe the image 21' formed by the display optical system 30 from the image information 21.

Since the size of the incident beam is small at the position of the entrance pupil P of the observer in this construction, the observer can observe a clear image of the image information 21, independent of the imaging performance of the eye optical system of the observer, on the basis of the principle similar to the so-called pinhole camera. Since the beam is incident to the eye without being intercepted even during the gaze at the marginal part of the field of the image information 21, it becomes feasible to implement the display and observation in the wide angle of view.

Fig. 4 to Figs. 9A to 9C show several configurations of specific operations of the illumination light source 11 of the illumination means 10.

For example, as illustrated in Fig. 4, the illumination light source 11 is comprised of a plurality of unit light sources 51 resulting from area-based division of the total area of the light source 11 into a plurality of regions. The incident beam control circuit 41 lights up each unit light source according to the position of the pupil of the observing eye.

The illumination light source 11 is constructed as a light-emitting element array such as an EL panel or an LED array, or in either of the configurations as illustrated in Figs. 5 to 8.

In Fig. 5, a unit light source 51 consists of a light-emitting element 52 and a pinhole 53 illuminated with a beam therefrom. Shield plates 54 are provided for preventing beams from adjacent light-emitting elements 52 from leaking into the light-emitting element 52 of interest.

In Fig. 6, a unit light source 51 consists of a light-emitting element 52 and a diffuser plate 55 illuminated by a beam therefrom. Shield plates 54 are provided for preventing beams from adjacent light-emitting elements from leaking into the light-emitting element of interest.

09032219.042001
FOUO 61222250

In Fig. 7, the illumination light source 11 consists of a surface emitting light source (surface illuminant) 56 such as a cold-cathode tube and a lightguide plate, or the like, and a transmission type spatial modulation element 57 such as a transmissive liquid crystal panel or the like. A unit light source 51 is comprised of one pixel or several pixels of the transmission type spatial modulation element 57.

In Fig. 8, the illumination light source 11 is comprised of a surface emitting light source (surface illuminant) 58, a lens 59, a half mirror 61, and a reflection type spatial modulation element 60 such as a reflective liquid crystal panel or the like. A unit light source 51 is comprised of one pixel (60a, 60b, or 60c) or several pixels of the reflection type spatial modulation element 60. Here light from the surface emitting light source 58 is reflected by the half mirror 61 to enter the spatial modulation element 60. The light optically modulated by the spatial modulation element 60 travels through the half mirror 61 to illuminate the image display means (see Fig. 1).

Another configuration of the illumination light source 11 can be realized by the structure illustrated in Figs. 9A to 9C. A side view of main part is presented on the left side while a front view of main part on the right side in each figure. The illumination light source 11 has a light source 62,

5 relation with a diffusing surface 64a of the diffuser
plate 64, the illumination light source 11 becomes a
light source having a light-emitting surface 11a of a
small area. As illustrated in Figs. 9B and 9C, the

illumination light source 11 can be varied by moving the illumination lens 63 or the light source 62 in the direction normal to the optical axis.

15 configurations of the illumination light source 11.

The unit sources do not have to be arranged in the
20 continuous array of unit sources as illustrated in Fig.
4, but they may also be arranged in a discrete pattern.

25 (Embodiment 1)

Fig. 10 is a schematic diagram to illustrate the main part of Embodiment 1 of the image observation

The light emitted from the illumination light source 11 of the illumination means 10 travels through a polarizer 33 to be converted into linearly polarized light. Part of the linearly polarized light is reflected by a half mirror 31 and then is guided to a lens 32 to be refracted thereby and guided to a display element 22 of the display means 20. The display element 22 is a reflection type display element such as a reflective liquid crystal panel having the pixel structure, which has, for example, a function of reflecting the linearly polarized light incident on pixels in "ON" display part while rotating the direction of polarization thereof by 90° but reflecting the linearly polarized light incident on pixels in "OFF" display part while preserving the direction of

polarization thereof.

The light reflected by the display element 22 is again refracted by the lens 32 and part thereof is transmitted by the half mirror 31 to be guided to a

5 polarizer 34. The polarizer 34 is placed so that the axis of transmitted polarization thereof is

perpendicular to that of the polarizer 33. Since the reflected light from the pixels in the "ON" display

10 part of the display element 22 has the direction of polarization rotated by 90° , it travels through the polarizer 34 to be guided to the observing eye E.

However, since the reflected light from the pixels in the "OFF" display part of the display element 22 has the direction of polarization preserved, it is

15 intercepted by the polarizer 34 and thus does not enter the observing eye E.

The display optical system 30 forms the image 11' of the illumination light source 11 at the position of the pupil P of the observing eye E. The size of the

20 illumination light source 11, the position and focal length of the display optical system 30, etc. are set so that the size of the illumination light source image 11' at this time is sufficiently smaller than the pupil P of the observing eye E. The observer observes the

25 image information displayed on the image display means 20 under illumination with the light from the illumination means 10.

05838219 042001

The incident beam control circuit 41 controls the illumination means 10, based on the image information and the output from the pupil position detecting means described hereinafter, to change the position of the light-emitting surface of the illumination light source 11, thereby changing the position of the incident beam at the pupil position of the observing eye E.

The reflection type display element 22 does not always have to be a liquid crystal panel, but may be a micromirror device or the like. When the display element 22 is the micromirror device, there is no need for use of the polarizers 33, 34.

The embodiment illustrated in Fig. 10 used the lens in the display optical system 30, but it may also be constructed using a reflector (concave mirror) having a curvature, such as a spherical surface, an aspherical surface, an ellipsoidal surface, a hyperboloidal surface, or the like, as illustrated in Fig. 11.

In Fig. 11, the elements having the same functions as those in the embodiment illustrated in Fig. 10 are denoted by the same reference symbols and the description thereof is omitted herein.

The light emitted from the illumination light source 11 of the illumination means 10 travels through the polarizer 33 to be converted into linearly polarized light, and part thereof is transmitted by the

half mirror 31 to be guided to the display element 22
of the display means 20. The light reflected by the
display element 22 is then reflected in part by the
half mirror 31, is reflected by the concave mirror 32,
5 and is transmitted in part again by the half mirror 31
to be guided to the polarizer 34. Just as in the
embodiment illustrated in Fig. 10, the reflected light
from the pixels in the "ON" display part of the display
element 22 is guided to the observing eye E, while the
10 reflected light from the pixels in the "OFF" display
part of the display element 22 does not enter the
observing eye E. Here the polarizers 33, 34 also have
a function of intercepting light emerging from the
illumination light source 11 and reflected toward the
15 observing eye E by the half mirror 33 to prevent it
from entering the observing eye E.

The incident beam control circuit 41 controls the
illumination means 10, based on the image information
and the output of the pupil position detecting means
20 described hereinafter, to change the position of the
light-emitting surface of the illumination light source
11, thereby changing the position of the incident beam
at the pupil position of the observing eye E.

In the embodiment illustrated in Figs. 10, 11, the
25 display element of the display means 20 was the
reflection type display element (spatial modulation
element), but the display element can be a transmission

0938219-042001

type display element (spatial modulation element) 23 as illustrated in Fig. 12.

In Fig. 12, the elements having the same functions as those in the embodiment illustrated in Figs. 10 and 11 are denoted by the same reference symbols and the description thereof is omitted herein. The illumination light emitted from the illumination light source 11 of the illumination means 10 is refracted by a lens 35 to be guided to the display element 23 of the display means 20. The display element 23 is the transmission type display element consisting of polarizers, a transmissive liquid crystal panel, and so on. The light transmitted by the display element 23 is guided to the observing eye E by the display optical system 30 including the half mirror 31 and the concave mirror 32.

The incident beam control circuit 41 controls the illumination means 10, based on the image information and the output of the pupil position detecting means described hereinafter, to change the position of the light-emitting surface of the illumination light source 11, thereby changing the position of the incident beam at the pupil position of the observing eye E.

This construction permits the observer to observe a clear image of the image information on the display means 20 according to the principle illustrated in Fig. 1, Fig. 2, and Fig. 3, and the beam is incident to the

eye without being intercepted even during the gaze at the marginal part of the field, thus enabling the display and observation in the wide angle of view. (Embodiment 2)

5 Fig. 13 is a schematic diagram to illustrate the major part of Embodiment 2 of the image observation apparatus according to the present invention. This apparatus, similar to the embodiment illustrated in Fig. 12, is generally provided with the illumination means 10 having the illumination light source 11, the image display means 20 for displaying the image information, the display optical system 30 for focusing the image of the illumination light source 11 of the illumination means 10 at or near the position of the pupil P of the observing eye E and directly projecting the image information displayed on the image display means 20 under illumination by the illumination means 10, onto the retina of the observing eye E, and the control means 40. The elements having the same functions as those in the embodiment illustrated in Fig. 12 are denoted by the same reference symbols and the description thereof is omitted herein.

 The illumination light emitted from the illumination light source 11 of the illumination means 10 is refracted by the lens 35 to be guided to the display element 23 of the display means 20. The light transmitted through the display element 23 enters a

100240-6122250

0933231042001
T002405T28350

prism body 36 while being refracted by a surface 36a thereof. The light entering the surface 36a of the prism body 36 is incident at an angle of incidence over the critical angle to a surface 36b to be totally internally reflected thereby. The light is then reflected by a mirror surface 36c and is incident at an angle of incidence below the critical angle this time to the surface 36b. Thus the light is refracted by the surface 36b to emerge from the prism body 36. Then the light is guided to the entrance pupil P of the observing eye E. The prism body 36 is configured to have at least one decentered, rotationally asymmetric surface with optical powers differing depending upon azimuth angles so as to well correct aberration caused by the tilted arrangement of its surfaces having their respective optical powers, thereby decreasing the size of the display optical system 30.

The incident beam control surface 41 controls the illumination means 10, based on the image information and the output of the pupil position detecting means described hereinafter, to change the position of the light-emitting surface of the illumination light source 11, thereby changing the position of the incident beam at the pupil position of the observing eye E.

In the embodiment illustrated in Fig. 13, the display element of the display means 20 can be replaced by a reflection type display element as illustrated in

Fig. 14. The elements having the same functions as those in the embodiments illustrated in Fig. 11 and in Fig. 13 are denoted by the same reference symbols and the description thereof is omitted herein.

5 In Fig. 14, the illumination light emitted from the illumination light source 11 of the illumination means 10 is refracted by the lens 35 and travels through the polarizer 33 to be converted into linearly polarized light. The linearly polarized light enters a
10 prism 37 while being refracted by a surface 37a thereof. The prism 37 is a triangular prism comprised of planes (which may also include a curved surface in part). The light entering the prism 37 is then incident at an angle over the critical angle to a
15 surface 37b to be totally internally reflected thereby. Then the light emerges from the prism 37 while being refracted by a surface 37c thereof and is then incident to the reflective display element 22. The light reflected by the reflective display element 22 is
20 incident to the prism 37 while being refracted by the surface 37c thereof. The light is again incident at an angle below the critical angle to the surface 37b and emerges from the prism 37 while being refracted thereby. The light is then incident to the polarizer
25 34. Just as in the embodiment illustrated in Fig. 11, the reflected light from the pixels in the "ON" display part of the display element 22 travels through the

0533219.042001

5

10

15

20

25

(Embodiment 3)

Embodiment 3 of the image observation apparatus of the present invention will be described below.

There are known self-emission type display devices like EL panels. There are also known light-source-integrated display devices of integrated structure of a back light, polarizers, a transmissive liquid crystal panel, and so on. In the present embodiment the image observation apparatus is constructed using the self-emission type or light-source-integrated display device, as illustrated in Fig. 15.

Fig. 15 is a schematic diagram to show the main part of Embodiment 3 of the image observation apparatus according to the present invention.

The image observation apparatus S according to the present invention has a self-emission type image display means 80 such as an EL panel for displaying the image information 81, a display optical system (eyepiece optical system) 90, a spatial modulation element 70, and the control means 40.

In Fig. 15, the light emitted from the image display means 80 travels through the spatial modulation element 70 and is guided to the observing eye E by the display optical system 90. The observer observes an image 81' formed by the display optical system 90 from the image information 81 displayed on the image display means 80.

5 The display optical system 90 forms an image 70' of the spatial modulation element 70 at the position of the pupil P of the observing eye. This permits the state of the incident beam at the position of the entrance pupil of the observer to be changed by controlling positions of transmitting and intercepting portions of the spatial modulation element 70.

10 The incident beam control circuit 41 controls the positions of the transmitting and intercepting portions of the spatial modulation element 70, based on the image information and the output of the pupil position detecting means described hereinafter, to change the position of the incident beam at the pupil position of the observing eye E.

15 This construction permits the observer to observe a clear image of the image information of the display means 80 in the manner similar to the principle illustrated in Fig. 1, Fig. 2, and Fig. 3, and enables the display and observation in the wide angle of view, because the beam is incident to the eye without being intercepted even during the gaze at the marginal part of the field.

(Embodiment 4)

25 Fig. 16 is a schematic diagram to show the main part of Embodiment 4 of the image observation apparatus according to the present invention. This apparatus has the self-emission type image display means 80 for

05032215-042001
100340-5122250

displaying the image information, the spatial modulation element 70, the display optical system 90 for guiding the image information to the observing eye E, and the control means 40.

5 The light emitted from the image information 81 displayed on the image display means 80 travels through a polarizer 93 to be converted into linearly polarized light. Part of the linearly polarized light is transmitted by a half mirror 91 to be guided to the

10 spatial modulation element 70. The spatial modulation element 70 is a reflection type spatial modulation element such as a reflective liquid crystal panel having the pixel structure, which has, for example, the function of reflecting the linearly polarized light

15 incident on the pixels in "ON" part while rotating the direction of polarization thereof by 90° but reflecting the linearly polarized light incident on the pixels in "OFF" part while preserving the direction of polarization thereof.

20 The light reflected by the spatial modulation element 70 is reflected in part by the half mirror 91 and is then reflected by a concave mirror 92 having a curvature. Part of the reflected light is transmitted by the half mirror 91 again to be guided to a polarizer

25 94. The polarizer 94 is placed so that its axis of transmitted polarization is perpendicular to that of the polarizer 93. Since the reflected light from the

090322-9 042004

5

10

15

25

In Fig. 17, the elements having the same functions as those in the embodiment illustrated in Fig. 16 are denoted by the same reference symbols and the description thereof is omitted herein. The light emitted from the image display device 80 is guided to the spatial modulation element 70 while being refracted by a lens 95. The spatial modulation element 70 is the transmission type spatial modulation element comprised of polarizers, a transmissive liquid crystal panel, and so on. The light transmitted through the spatial modulation element 70 is guided to the observing eye E by the display optical system 90 consisting of the half mirror 91 and the concave mirror 92. The display optical system 90 forms the image 70' of the spatial modulation element 70 at the position of the pupil P of the observing eye E.

The incident beam control circuit 41 controls the positions of the transmitting and intercepting portions of the spatial modulation element 70, based on the image information and the output of the pupil position detecting means described hereinafter, to change the position of the incident beam at the pupil position of the observing eye E.

This construction permits the observer to observe a clear image in the manner similar to the principle illustrated in Fig. 1, Fig. 2, and Fig. 3, and enables the display and observation in the wide angle of view, because the beam is incident without being intercepted even during the gaze at the marginal part of the field.

Fig. 18 and Figs. 19A, 19B show a specific configuration of the pupil position detecting system (pupil position detecting means) used in each embodiment. In Fig. 18 the pupil position detecting system 150 has an eyeball illuminating means 151, a light receiving means 152 for receiving reflected light by the observing eye E from the illumination light emitted from the eyeball illuminating means 151, and an arithmetic means 153. The pupil position detecting system 150 is located at a position where the system does not interfere with the optical paths and the like of the display optical system for observation of the image, for example, at a position in the vertical direction in the case of Fig. 18. The eyeball illuminating means 151 is an infrared LED or the like. Use of infrared light permits the pupil position to be detected without affecting the observation of image.

The light receiving means 152 is composed of a lens and an image pickup device such as a CCD or the like. Figs. 19A and 19B show images of the observing eye E received by the light receiving means 152.

Intensities of reflected light from respective portions of the observing eye E become weaker in the order of skin of palpebra and the like, sclera, iris I, and pupil P. Therefore, the arithmetic means 153 extracts the darkest portion in the received image and calculates the position of the center thereof to detect the pupil position. Fig. 19A shows a situation in which the observer is gazing at the central part of the field, and Fig. 19B a situation in which the observer is gazing at the marginal part of the field (or looking aside).

The method of detecting the pupil position can be a method of detection using reflected light from the retina, and the light receiving element can be one selected from a line sensor, a PSD, a quatrefoil sensor, and so on.

The pupil position detecting means 150 sends the information of the detected pupil position to the incident beam control means 41, as illustrated in Fig. 20A, and the incident beam control means 41 controls the illumination means 10 or the spatial modulation element 70, based on the information, as described in each of the embodiments described above. In another configuration, as illustrated in Fig. 20B, the control means can also be configured to automatically determine the direction of the visual axis of the observer, e.g., from the position of an image including a high-

frequency component in the screen, based on the image
information from the image input means, calculate an
estimated pupil position, and control the illumination
means 10 or the spatial modulation element 70, based
5 thereon.

Further, when a pair of image observation devices
S as described in each of the above embodiments are
provided for the left and right eyes of the observer as
illustrated in Fig. 36, it becomes feasible to
10 implement the stereoscopic vision using the binocular
parallax and to provide an image observation system
such as a head-mounted display or the like being
capable of reducing the contradiction between
convergence and accommodation of the observing eyes,
15 which can occur during observation of the stereoscopic
image by use of only the binocular parallax, because
the focus states of the observed images are independent
of the accommodation of the eyes, and thus permitting
the observer to observe the stereoscopic image well in
20 the natural state. In particular, since the beam is
incident on the eye without being intercepted even
during the gaze at the marginal part of the field in
the construction using the image observation apparatus
of the present invention, it becomes feasible to
25 implement the display and observation in the wide angle
of view and reproduce the space in the wide range in
the depth direction.

FIG. 36

According to the present invention, as described above, during the observation of the image information displayed on the image display means the beam is incident on the eyeball without being intercepted by the iris even during the gaze at the marginal part of the field with rotation of the eyeball from the center of the field whereby it becomes feasible to implement the display and observation in the wide angle of view and whereby the space can be reproduced in the wide range in the depth direction during the observation of the stereoscopic image. Therefore, the present invention can accomplish the image observation apparatus and the image observation systems using the apparatus.

Fig. 21 to Fig. 24 are explanatory diagrams to illustrate the basic concept in further embodiments of the image observation apparatus of the present invention. The image observation apparatus S according to the present invention is generally provided with the illumination means 10 having the illumination light source 11 comprised of a plurality of unit light sources, the image display means 20 for displaying the image information 21 including parallax images, the display optical system 30, and the control means 40.

In Fig. 21, the illumination means 10 is located at or near the position Pa of the entrance pupil of the display optical system 30 and the display optical

5 The observer substantially aligns the entrance pupil P of the eye E with the exit pupil Pb of the display optical system 30 (to such an extent that the observer can observe the image, which also applies to the following), whereby the observer observes the image (enlarged virtual image) 21' formed by the display optical system 30 from the image information 21 displayed on the image display means 20 under illumination by the illumination means 10. The position, the focal length, etc. of the display optical system 30 are determined so that the enlarged virtual image of the display element surface of the image display means 20 is focused, for example, 2 m ahead of the eye E.

A method of sequentially injecting a plurality of
20 parallax images into a single eye E will be described
below with reference to Figs. 22 to 24. Figs. 22 to 24
are top plan views of the image observation apparatus S
according to the present invention. Figs. 22 to 24
show a case for displaying three parallax images in the
25 horizontal direction for simplicity, but it is noted
that the number of parallax images is not limited to
this number and that an arbitrary number of parallax

images can be injected based on the display view angle, resolving power, and so on, including a plurality of parallax images in the vertical direction. For example, the apparatus may be constructed in a structure to inject totally twelve parallax images, i.e., four parallax images horizontal by three parallax images vertical.

The illumination light source 11 is composed of a plurality of unit light sources 11a, 11b, 11c, which are sequentially lighted up (in time series) by the control means 40, as illustrated in Figs. 22 to 24. An image of each light source 11a to 11c is formed in each area 11a' to 11c' of the exit pupil Pb. This results in spatially dividing the exit pupil Pb of the display optical system 30 into a plurality of regions (11a', 11b', 11c'), and it thus becomes feasible to control the beam incident on each region 11a' to 11c' in time division. At this time the control means 40 switches the image information 21 displayed on the image display means 20 among parallax image information pieces 21a, 21b, 21c in response to the above switching of the unit light sources. The image information pieces 21a, 21b, 21c are small parallax images obtained (or observed) when the view point is located at the position of the center of each region 11a', 11b', 11c' on the pupil plane P to view the reproduced object. Since the switching operations of the light source 11 and the

100240"6T222250

image information 21 synchronized therewith by the control means 40 are repeatedly carried out in shorter periods than the permissible time of persistence of vision for the observer's eye, the switching operations
5 can be performed without being perceived by the observer.

The illumination light source 11 consisting of the plurality of unit light sources 11a to 11c of the illumination means 10 has the structure as illustrated
10 in Fig. 25A. As illustrated in Fig. 25A, the illumination light source 11 is composed of a plurality of unit light sources 51 resulting from region-based division of the total area. Fig. 25A shows a case in which the size of the exit pupil Pb of the display
15 optical system is, for example, 10.5 mm x 10.5 mm and intervals between centers of segmental regions in the entrance pupil P of the observing eye E are 1.5 mm, in consideration of the display view angle, resolving power, and so on, and thus there are totally forty nine
20 parallax images, i.e., seven parallax images horizontal by seven parallax images vertical. The unit light sources 51 correspond to the unit light sources 11a, 11b, 11c in Fig. 22 to Fig. 24. In the conventional image observation apparatus, it was necessary to
25 repeatedly carry out the operation of sequentially lighting up all the forty nine unit sources 51 and switching the parallax images displayed on the image

09838219-012001
T00240-6T282850

display means 20 in synchronism therewith in the periods shorter than the permissible time of persistence of vision for eye. When the display view angle is small and thus the number of parallax images to be presented to the observing eye is small, there is no need for use of the image display means operating at so high speed. However, the image display means operating at very high speed had to be used in order to display the forty nine parallax images as illustrated in Fig. 25A, in the periods shorter than the permissible time of persistence of vision for eye.

In the image observation apparatus according to the present invention, the control means 40 does not light all the plurality of unit light sources 51 constituting the illumination light source 11 in time division, but selectively lights unit light sources according to the pupil position of the observing eye E, based on the displayed image information and the information from the pupil position detecting means described hereinafter. This will be described referring to Figs. 25B and 25C. Figs. 25B and 25C show the illumination light source 11 and in the figures P' represents a projected image at the position of the illumination light source 11 by the display optical system 30 from the pupil P of the observing eye E.

For example, when the observer is gazing at the central part of the field as illustrated in Fig. 25B,

the control means successively lights up only nine unit sources 51a (hatched in the figure) corresponding to the position and size of the projected image P' of the pupil P and displays parallax images corresponding to the positions of the respective unit sources in the image display means 20 in synchronism therewith. When the observer is gazing at the marginal part of the field as illustrated in Fig. 25C, similarly, the control unit also successively lights up only nine unit sources 51a (hatched in the figure) corresponding to the position of the projected image P' of the pupil P and displays parallax images corresponding to the positions of the respective unit sources in the image display means 20 in synchronism therewith.

In the structure as described above, the number of parallax images displayed on the image display means 20 is always nine and is greatly decreased, thus permitting construction of the image observation apparatus of the wide field angle without need for use of the very quick image display means.

In the example illustrated in Figs. 25A to 25C, the illumination light source is composed of the forty nine unit light sources from the beginning and they are selectively and successively lighted up, but the illumination light source can also be constructed in such structure that it is composed of nine unit light sources of 3×3 and the illumination light source

Further, since influence of parallax in the horizontal direction is stronger than that in the vertical direction in the stereoscopic vision, it becomes feasible to further decrease the number of parallax images to be displayed, by setting the number of parallax images in the vertical direction smaller than the number of parallax images in the horizontal direction. For example, Fig. 26A shows a configuration in which the number of unit light sources 51 making the illumination light source 11 is 21 in total, 7 horizontal and 3 vertical, which can also achieve a like effect even in the number smaller than that in the configuration illustrated in Fig. 25A. The control means 40 selectively lights the unit light sources corresponding to the position of the projected image P' of the pupil P of the observer in the same manner as in the method illustrated in Figs. 25B and 25C, to present parallax images to the observing eye.

It is noted that all the unit light sources 51a corresponding to the position of the projected image of the pupil P on the illumination light source 11 do not have to be lighted up and an arbitrary number of unit
25 light sources may be further selected and lighted up out of the unit light sources corresponding to the pupil position to be presented to the observing eye.

In an example, in Fig. 26C, there are six unit light sources 51a corresponding to the position of the projected image P' of the observer's pupil P, and only three out of them are selectively successively lighted up. In a further example, in Figs. 25B and 25C, six unit light sources are selectively and successively lighted up. These configurations can simplify the structure of the apparatus, because the number of parallax images to be displayed is fixed regardless of the pupil position of the observing eye.

In Fig. 25B, the size of the exit pupil of the display optical system is one enough to cover all the illumination light source 11, the unit light sources to be lighted are only in the portion of 51a corresponding to the size of the entrance pupil of the observing eye, and the size of the beam from the image display means at the position of the entrance pupil of the observing eye illuminated by the light source is equal to or smaller than the size of the entrance pupil of the observing eye.

As described above, the size of the exit pupil of the display optical system is set larger than the pupil of the observing eye and only the display beam corresponding to the pupil position of the observing eye is generated by control of the light source as illustrated in Figs. 25A to 25C and Figs. 26A to 26C, whereby the size of the beam from the image display

means at the position of the entrance pupil P of the observing eye becomes substantially equal to or smaller than the size of the entrance pupil P of the observing eye, thus enabling the stereoscopic display of the "super-multiview regions" in the wide angle of view without need for use of the very quick image display means.

It is also feasible to implement the display and observation in the wide angle of view when the illumination light source 11 in the present embodiment is replaced by that of the configuration illustrated in Fig. 27A. As illustrated in Fig. 27A, the area of each of the four unit light sources 51c in the outermost periphery region constituting the illumination light source 11 is set wider than that of each of the unit light sources 51b other than those in the outermost periphery region. The control means successively lights up the unit light sources 51b, 51c (totally seven sources in the example illustrated in Fig. 27A) and displays the parallax images corresponding to the positions of the respective unit light sources in the image display means in synchronism therewith. This construction permits the observer to observe the image with the display beam entering the pupil P of the observing eye E, regardless of where the observer is gazing in the field, as illustrated in Figs. 27B and 27C, without need for setting the number of parallax

images to be presented to the observing eye, to a large value, and thus enables the stereoscopic display of the "super-multiview regions" in the wide angle of view without need for use of the very quick image display means.

As described above, the present embodiment is arranged to spatially divide the exit pupil of the display optical system into the plurality of regions, cause the plurality of parallax images corresponding to the positions of the respective regions to be incident on the observing eye so as to guide the plurality of parallax images into the single eye of the observer, and set the area of the regions in the outermost periphery among the plurality of regions of the exit pupil to be larger than the area of the regions except for the regions in the outermost periphery, thereby permitting the observation of the stereoscopic image in good order.

The illumination light source 11 is comprised of a light-emitting element array such as an EL panel or an LED array, or constructed in either of the structures as illustrated in Figs. 5 to 8.

Embodiments of the image observation apparatus of the present invention will be detailed below.

(Embodiment 5)

Fig. 28 is a schematic diagram to illustrate the main part of Embodiment 5 of the image observation

apparatus according to the present invention. This apparatus is generally provided with the illumination means 10 having the illumination light source 11 consisting of a plurality of unit light sources, the
5 image display means 20 for displaying the image information, the display optical system 30 for guiding the image information displayed on the image display means 20 under illumination with the light from the illumination means 10, to the observing eye E, and the
10 control means 40.

The light emitted from the plurality of unit light sources of the illumination means 10 travels through the polarizer 23 to be converted into linearly polarized light. Part of the linearly polarized light
15 is transmitted through the half mirror 31 to be guided to the display element 25. The display element 25 is a reflection type display element such as a reflective liquid crystal panel having the pixel structure or the like, which has, for example, the function of
20 reflecting the linearly polarized light incident on the pixels in the "ON" display part while rotating the direction of polarization thereof by 90° but reflecting the linearly polarized light incident on the pixels in the "OFF" display part while preserving the direction
25 of polarization thereof.

The light reflected by the display element 25 is reflected in part by the half mirror 31 and the

09532219-042001

reflected light is reflected by the concave mirror 32 having a curvature, such as a spherical surface, an aspherical surface, an ellipsoidal surface, a hyperboloidal surface, or the like. The light is transmitted in part through the half mirror 31 to be guided to the polarizer 24. The polarizer 24 is arranged so that the axis of transmitted polarization thereof is perpendicular to that of the polarizer 23. The reflected light from the pixels in the "ON" display part of the display element 25 is transmitted by the polarizer 24 to be guided to the observing eye E, because the direction of polarization thereof is rotated by 90°. However, the reflected light from the pixels in the "OFF" display part of the display element 25 is not incident on the observing eye E while being intercepted by the polarizer 24, because the direction of polarization thereof is preserved. The polarizer 24 also has the function of intercepting the light emitted from the illumination light source 11, transmitted through the polarizer 23, and reflected in part toward the observing eye E by the half mirror 31, so as to prevent it from entering the observing eye E.

The illumination light source 11 is located at or near the position Pa of the entrance pupil of the display optical system 30 and the display optical system 30 forms an image of the illumination light source 11 at or near the exit pupil Pb of the display

optical system 30 being in the conjugate relation with the entrance pupil. The observer approximately aligns the entrance pupil P of the eye with the exit pupil Pb of the display optical system 30 whereby the observer
5 observes the image formed by the display optical system 30 from the image information displayed on the image display means 20 under illumination by the illumination light source 11. The position, the focal length, etc. of the display optical system 30 are determined so that
10 it forms an enlarged virtual image of the display element surface of the image display means 20, for example, 2 m ahead of the entrance pupil P.

The control means 40 performs control to appropriately switch the illumination light source 11
15 and the display element 25 in time division to cause a plurality of parallax images to be incident on the single eye of the observer, based on the principle illustrated in Figs. 21 to 24, 25A to 25C, 26A to 26C and 27A to 27C, thereby enabling the stereoscopic
20 display of the "super-multiview regions" in the wide angle of view.

The embodiment illustrated in Fig. 28 used the reflection type display element (spatial modulation element) as the display element of the display means
25 20, but the transmission type display element (spatial modulation element) 26 can also be employed as illustrated in Fig. 29.

In Fig. 29, the elements having the same functions as those in the embodiment illustrated in Fig. 28 are denoted by the same reference symbols and the description thereof is omitted herein. The

5 illumination light emitted from the illumination light source 11 of the illumination means 10 is refracted by a condenser lens 12 to be guided to the display element 26 of the display means 20. The display element 26 is a transmission type display element composed of

10 polarizers, a transmissive liquid crystal panel, and so on. The light transmitted through the display element 26 is guided to the observing eye E by the display optical system 30 consisting of the half mirror 31 and the concave mirror 32. The focal length, the position, etc. of the condenser lens 12 are determined so that

15 the position 11b of the image of the illumination light source 11 by the condenser lens 12 is coincident with the position Pa of the entrance pupil of the display optical system 30. The display optical system 30 forms

20 the image of the illumination light source 11 at the position of the exit pupil Pb thereof. The observer substantially aligns the entrance pupil P of the eye with the exit pupil Pb of the display optical system 30 whereby the observer observes the image formed by the

25 display optical system 30 from the image information displayed on the image display means 20 under illumination by the illumination light source 11.

100240 6128250

The control means 40 performs the control to properly switch the illumination light source 11 and the display element 26 in time division, so as to cause a plurality of parallax images to be incident on the single eye of the observer, based on the principle illustrated in Figs. 21 to 24, 25A to 25C, 26A to 26C and 27A to 27C, thereby enabling the stereoscopic display of the "super-multiview regions" in the wide angle of view.

(Embodiment 6)

Fig. 30 is a schematic diagram to illustrate the main part of Embodiment 6 of the image observation apparatus according to the present invention. Just as in the embodiment illustrated in Fig. 29, this apparatus is generally provided with the illumination means 10 having the illumination light source 11 consisting of a plurality of unit light sources, the image display means 20 for displaying the image information, the display optical system 30 for guiding the image information displayed on the image display means 20 under illumination by the illumination means 10, to the observing eye E, and the control means 40. The elements having the same functions as those in the embodiment illustrated in Fig. 29 are denoted by the same reference symbols and the description thereof is omitted herein.

The illumination light emitted from the plurality

of illumination light sources 11 in the illumination means 10 is refracted by the condenser lens 12 to be guided to the display element 26 of the display means 20. The light transmitted through the display element 26 is incident to a prism body 33 while being refracted by a surface 34 thereof. The light entering the prism body 33 is incident at an angle of incidence over the critical angle on a surface 35 thereof to be totally internally reflected thereby. The light is then reflected by a mirror surface 36 and is again incident at an angle of incidence below the critical angle on the surface 35 to emerge from the prism body 33 while being refracted thereby. The emerging light is guided to the entrance pupil P of the observing eye E. The prism body 33 is configured so as to have at least one decentered, rotationally asymmetric surface with optical powers differing depending upon azimuth angles in order to well correct the aberration caused by the tilted arrangement of the surfaces having their respective optical powers, thereby decreasing the size of the display optical system 30. The position, the focal length, etc. of the prism body 33 are determined so that it forms an enlarged virtual image of the display element surface of the display means 20, for example, 2 m ahead of the entrance pupil P.

The display optical system 30 forms the image of the illumination light source 11 at the position Pb of

0988219-042001

the exit pupil thereof. The observer substantially aligns the entrance pupil P of the eye with the exit pupil Pb of the display optical system 30 whereby the observer observes the image formed by the display optical system 30 from the image information displayed on the image display means 20 under illumination by the illumination light source 11.

The control means 40 performs the control to properly switch the illumination light source 11 and the display element 26 in time division, so as to cause a plurality of parallax images to be incident on the single eye of the observer, based on the principle illustrated in Figs. 21 to 24, 25A to 25C, 26A to 26C and 27A to 27C, thereby enabling the stereoscopic display of the "super-multiview regions" in the wide angle of view.

In the embodiment illustrated in Fig. 30, the display element of the display means 20 can be a reflection type display element as illustrated in Fig. 31. The elements having the same functions as those in the embodiments illustrated in Fig. 28 and Fig. 30 are denoted by the same reference symbols and the description thereof is omitted herein.

In Fig. 31, the illumination light emitted from the illumination light source 11 of the illumination means 10 is refracted by the condenser lens 12 and travels through the polarizer 23 to be converted into

linearly polarized light. The linearly polarized light is incident to a prism 13 while being refracted by a surface 14 thereof. The prism 13 is a triangular prism composed of planes (which may include a curved surface in part). The light entering the prism 13 is incident at an angle over the critical angle on a surface 15 to be totally internally reflected thereby. The reflected light is then refracted by a surface 16 to emerge from the prism 13. The emerging light is incident to the reflection type display element 25. The light reflected by the reflection type display element 25 is incident to the prism 13 while being refracted by the surface 16 thereof. Then the light is again incident at an angle below the critical angle to the surface 15 to emerge from the prism 13 while being refracted thereby. The emerging light is then incident to the polarizer 24. Just as in the embodiment illustrated in Fig. 28, the reflected light from the pixels in the "ON" display part of the display element 25 is transmitted through the polarizer 24, while the reflected light from the pixels in the "OFF" display part of the display element 25 is intercepted by the polarizer 24. The light transmitted through the polarizer 24 is guided to the observing eye E while being reflected and refracted in the same manner as described in Fig. 30, by the prism body 33. The size of the apparatus is decreased by constructing the

illumination means 10 by use of the total internal reflection in the prism 13. In the present embodiment the surface 15 of the prism 33 is the total internal reflection surface, but it may also be a half mirror surface or a polarization beam splitter surface.

The display optical system 30 forms the image of the illumination light source 11 at the position Pb of the exit pupil thereof. The observer substantially aligns the entrance pupil P of the eye with the exit pupil of the display optical system 30 whereby the observer observes the image formed by the display optical system 30 from the image information displayed on the image display means 20 under illumination by the illumination light source 11.

The control means 40 performs the control to properly switch the illumination light source 11 and the display element 25 in time division, so as to cause a plurality of parallax images to be incident on the single eye of the observer, based on the principle illustrated in Figs. 21 to 24, 25A to 25C, 26A to 26C and 27A to 27C, thereby enabling the stereoscopic display of the "super-multiview regions" in the wide angle of view.

In the embodiments illustrated in Fig. 28 to Fig. 31, the illumination light source and display element were controlled by time-division switching at high speed in order to cause the plurality of parallax

09333333 0430004

images to be incident on the observing eye, but a like effect can also be attained by provision of a plurality of display means.

(Embodiment 7)

5 Fig. 32 is a schematic diagram to show the main part of Embodiment 7 of the image observation apparatus of the present invention. This apparatus has a plurality of illumination light sources 71a, 71b, 71c, a plurality of display means 81a, 81b, 81c
10 corresponding to the respective illumination light sources, and the display optical system 90.

 The light emitted from the illumination light source 71a travels through the transmission type display element 81a and is reflected in part by a half
15 mirror 95. The reflected light travels while being converged by optical elements 96, 97, and part thereof is transmitted through a half mirror 99 to be guided to the observing eye E. A half mirror coat is laid on one surface 98 forming the optical element 97. The light
20 emitted from the illumination light source 71b travels through the transmission type display element 81b and part thereof is transmitted through the half mirror 95. Just as in the case of the light from the illumination light source 71a, the transmitted light travels through
25 the optical elements 96, 97 and through the half mirror 99 to the observing eye E. The light emitted from the illumination light source 71c travels through the

0333219-042001

The observer substantially aligns the entrance pupil P of the eye with the exit pupil of the display optical system 90 whereby the observer observes the image formed by the display optical system 90 from the image information displayed on the transmission type display element 81a, 81b, 81c under illumination by the illumination light source 71a, 71b, 71c. The position, the focal length, etc. of the display optical system 90 are determined so that it forms enlarged virtual images of the display element surfaces of the transmission type display elements 81a, 81b, 81c, for example, 2 m ahead of the entrance pupil P.

The observer substantially aligns the entrance pupil P of the eye with the exit pupil of the display optical system 90 whereby the observer observes the image formed by the display optical system 90 from the image information displayed on the transmission type display element 81a, 81b, 81c under illumination by the illumination light source 71a, 71b, 71c. The position, the focal length, etc. of the display optical system 90 are determined so that it forms enlarged virtual images of the display element surfaces of the transmission type display elements 81a, 81b, 81c, for example, 2 m ahead of the entrance pupil P.

The transmission type display elements 81a, 81b, 81c display parallax images corresponding to the respective images 71a', 71b', 71c' of the illumination light sources.

5 As described above, the apparatus of the present embodiment is provided with a plurality of display means to cause a plurality of parallax images to be incident on the single eye of the observer without use of quick image display means, thereby enabling the
10 stereoscopic display of the "super-multiview regions."

 In the embodiment illustrated in Fig. 32, a method for display of color image can be either selected from a method of constructing the illumination light sources 71a, 71b, 71c of white light sources and the display
15 elements 81a, 81b, 81c of panels equipped with a color filter, a method of constructing the illumination light sources 71a, 71b, 71c, e.g., of light sources of red, green, and blue and the display elements 81a, 81b, 81c of monochromatic display panels, and so on.

20 In Fig. 32, it is also possible to increase the number of parallax images presented to the observing eye, by constructing each of the illumination light sources 71a, 71b, 71c of a plurality of unit light sources as illustrated in Figs. 25A to 25C, 26A to 26C
25 and 27A to 27C, driving the display elements 81a, 81b, 81c in time division, and properly controlling the lighting of the unit light sources and the display

09838219 042001
T00240 6728260

images of the display elements.

(Embodiment 8)

Embodiment 8 of the image observation apparatus according to the present invention will be described
5 below.

There are known quick display devices of the self-emission type like EL panels. There are also known display devices of the light source integrated type in which a back light, polarizers, a transmissive liquid
10 crystal panel, etc. are integrated. In the present embodiment the image observation apparatus is constructed as illustrated in Fig. 33, using such a self-emission type or light-source-integrated display device.

Fig. 33 is a schematic diagram to show the main part of Embodiment 8 of the image observation apparatus according to the present invention.

The image observation apparatus S according to the present invention has the self-emission type image
20 display means 110 such as an EL panel for displaying the image information 111, a relay optical system 120, the display optical system (eyepiece optical system) 130, a spatial modulation element 100, and the control means 40.

In Fig. 33, the image information 111 displayed on the image display means 110 is focused as an aerial image 111' by the relay optical system 120 and is

further focused as an enlarged virtual image 111" by the display optical system 130. The observer substantially aligns the entrance pupil P of the eye with the exit pupil of the display optical system 130 to observe the image 111". The positions, the focal lengths, and so on of the relay optical system 120 and the display optical system 130 are determined so that they form the enlarged virtual image 111" of the image information 111, for example, 2 m ahead of the entrance pupil P.

The spatial modulation element 100 is located at or near the position Pa of the entrance pupil of the display optical system 130, and the display optical system 130 forms an image 100' of the spatial modulation element 100 at or near the position Pb of the exit pupil of the display optical system 130 being in the conjugate relation with the entrance pupil. This permits the state of the incident beam at the position of the entrance pupil of the observer to be changed by controlling positions and areas of the transmitting and intercepting portions of the spatial modulation element 100.

The control means 40 performs the control to properly switch the spatial modulation element 100 and the image display means 110 in time division, so as to inject a plurality of parallax images into the single eye of the observer, based on the principle illustrated

in Figs. 21 to 24, 25A to 25C, 26A to 26C and 27A to 27C, thereby enabling the stereoscopic display of the "super-multiview regions" in the wide angle of view. (Embodiment 9)

5 Fig. 34 is a schematic diagram to show the main part of Embodiment 9 of the image observation apparatus according to the present invention. This apparatus has the self-emission type image display means 110 for displaying the image information, the relay optical
10 system 120, the spatial modulation element 100, the display optical system 130 for guiding the image information to the observing eye E, and the control means 40.

 The light emitted from the image display means 110
15 is converged by a relay lens 121 of the relay optical system 120 and then travels through a polarizer 141 to be converted into linearly polarized light. The linearly polarized light is transmitted in part through a half mirror 131 and the transmitted light is guided
20 through a field lens 122 to the spatial modulation element 100. The spatial modulation element 100 is a reflection type spatial modulation element such as a reflective liquid crystal panel having the pixel structure, which has, for example, the function of
25 reflecting the linearly polarized light incident on the pixels in the "ON" part while rotating the direction of polarization by 90° but reflecting the linearly

0933213-042001
10040-6128550

polarized light incident on the pixels in the "OFF" part while preserving the direction of polarization thereof.

5 The light reflected by the spatial modulation element 100 forms an aerial image of the image display means 110 and is reflected in part through the half mirror 131. The reflected light is reflected by a concave mirror 132 to be transmitted in part by the half mirror 131 again, and then is guided to a

10 polarizer 142. The polarizer 142 is arranged so that its axis of transmitted polarization is perpendicular to that of the polarizer 141. Since the reflected light from the pixels in the "ON" part of the spatial modulation element 100 has the direction of

15 polarization rotated 90° , it travels through the polarizer 142 to be guided to the observing eye E. However, since the reflected light from the pixels in the "OFF" part of the spatial modulation element 100 has the direction of polarization preserved, it is

20 intercepted by the polarizer 142, so as not to enter the observing eye E. The polarizer 142 also has the function of intercepting the light emitted from the image display means 110, transmitted through the polarizer 141, and partly reflected toward the

25 observing eye E by the half mirror 131, so as to prevent it from entering the observing eye E.

The spatial modulation element 100 is located at

the position of the entrance pupil of the display
optical system 130, and the display optical system 130
forms an image of the spatial modulation element 100 at
the position of the exit pupil of the display optical
5 system 130 being in the conjugate relation with the
entrance pupil. The observer substantially aligns the
entrance pupil P of the eye with the exit pupil of the
display optical system 130 whereby the observer
observes the image formed by the relay optical system
10 120 and the display optical system 130 from the image
information displayed on the image display means 110.
The positions, the focal lengths, etc. of the relay
optical system 120 and the display optical system 130
are determined so that they form an enlarged virtual
15 image of the display element surface of the image
display means 110, for example, 2 m ahead of the
entrance pupil P.

The control means 40 performs the control to
properly switch the spatial modulation element 100 and
20 the image display means 110 in time division, so as to
cause a plurality of parallax images to be incident on
the single eye of the observer, based on the principle
illustrated in Figs. 21 to 24, 25A to 25C, 26A to 26C
and 27A to 27C, thereby enabling the stereoscopic
25 display of the "super-multiview regions" in the wide
angle of view.

Since the imaging relation of the pupil can be

separated from the imaging relation of the image display means by the use of the field lens 122, it increases degrees of freedom of layout and facilitates decrease of size of apparatus and the like.

5 In the embodiment illustrated in Fig. 34, the spatial modulation element 100 was the reflection type element, but a transmission type spatial modulation element 100 may also be used as illustrated in Fig. 35.

10 In Fig. 35, the elements having the same functions as those in the embodiment illustrated in Fig. 34 are denoted by the same reference symbols and the description thereof is omitted herein. The light emitted from the image display device 110 is guided to the spatial modulation element 100 while being
15 converged by the relay optical system 120. The spatial modulation element 100 is the transmission type spatial modulation element consisting of polarizers, a transmissive liquid crystal panel, and so on. The light transmitted through the spatial modulation
20 element 100 is guided to the observing eye E by the display optical system 130 consisting of the half mirror 131 and the concave mirror 132. The display optical system 130 forms an image of the spatial
25 modulation element 100 at the position of the exit pupil thereof. The observer substantially aligns the entrance pupil P of the eye with the exit pupil of the display optical system 130 whereby the observer

The control means 40 performs the control to properly switch the spatial modulation element 100 and the image display means 110 in time division, so as to cause a plurality of parallax images to be incident on the single eye of the observer, based on the principle illustrated in Figs. 21 to 24, 25A to 25C, 26A to 26C and 27A to 27C, thereby enabling the stereoscopic display of the "super-multiview regions" in the wide angle of view.

The pupil position detecting means 150 sends the detected information of pupil position to the control means 40, and the control means 40 controls the illumination means 10 and display means 20, or the spatial modulation element 100 and the display means 110, based on the information.

In another configuration, the control means 40 can be configured to automatically determine the direction of the visual axis of the observer, e.g., from a position of an image including a high-frequency component in the screen, based on the image information

5 Further, when a pair of image observation devices
S in each of the above embodiments are provided for the
left and right eyes of the observer as illustrated in
Fig. 36, it becomes feasible to implement the
stereoscopic vision including the binocular parallax
10 and to present a plurality of parallax images to the
observing eyes. Therefore, the apparatus can reduce
the fatigue due to the contradiction between
convergence and accommodation of the observing eyes,
which can occur during the observation of the
15 stereoscopic image by use of only the binocular
parallax, and permits the observer to observe the
stereoscopic image well in the natural state.
Particularly, in the construction using the image
observation apparatus of the present invention, the
20 beam is incident on the eye without being intercepted
even during the gaze at the marginal part of the field,
and it thus becomes feasible to implement the display
and observation in the wide angle of view and to
reproduce the space in the wide range in the depth
25 direction.

In the case wherein a pair of image observation devices according to the present invention are provided

for the left and right eyes as illustrated in Fig. 36,
when the gazing position is further outside that
illustrated in Fig. 27C, the plurality of parallax
images fail to enter the observing eyes, but the
5 stereoscopic image can be observed at least by the
binocular parallax.

In each of the above embodiments the phrase
"spatially divide the exit pupil of the display optical
system into a plurality of regions" means as follows;
10 in Embodiments 5 to 7, the illumination light source
located at the position of the entrance pupil of the
display optical system is comprised of a plurality of
unit light sources as illustrated in Figs. 25A to 25C
whereby the images of the unit light sources formed on
15 the exit pupil spatially divide the exit pupil into a
plurality of regions; in Embodiments 8 and 9, the
spatial modulation element having the two-dimensional
pixel structure is located at the position of the
entrance pupil of the display optical system whereby
20 the images of the respective pixels of the spatial
modulation element formed on the exit pupil spatially
divide the exit pupil into a plurality of regions.

The control means to change the position of the
beam from the image display means at the position of
25 the entrance pupil of the observing eye is to change
the position of the beam from the light source
illuminating the image display means in Embodiments 5

100240"6T28E260

to 7. In Embodiments 8, 9, the position of the beam from the image display means is changed by the spatial modulation element provided in the optical path, using the self-emission type image display means.

5 The present invention is able to achieve the image observation apparatus being capable of implementing the stereoscopic display of the super-multiview regions in the wide angle of view and permitting the observer to well observe the stereoscopic image without fatigue nor
10 dysphoria, and the image observation systems using the apparatus.

 In addition, the present invention makes it feasible to implement the stereoscopic display of the "super-multiview regions" in the wide angle of view
15 without need for use of the very quick image display means and image generating means nor many image display means, to simplify and compactify the apparatus, and free the observer from the fatigue and dysphoria during observation.

0933219-04001
100240-6128260